



Designing recurrent cells to enforce stability in real-time dynamical simulations

Louen Pottier, Anders Thorin

► To cite this version:

Louen Pottier, Anders Thorin. Designing recurrent cells to enforce stability in real-time dynamical simulations. IUTAM Symposium on Data-driven mechanics, Oct 2022, Paris, France. hal-04048373

HAL Id: hal-04048373

<https://hal.science/hal-04048373v1>

Submitted on 27 Mar 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



HAL Authorization

Designing recurrent cells to enforce stability in real-time dynamical simulations

POTTIER Louen, THORIN Anders
CEA List, Palaiseau (contact : louen.pottier@cea.fr)


Context

Interactive simulation in structural dynamics

- Interactivity $\Rightarrow$ evolution of mechanical loading not known in advance
- Need to quickly solve the equations of dynamics


Surrogate model

- Substitution of the slow physical model by a less expensive model trained using some datas generated with the physical model
- « Black box » model, loss of physical sense in favor of speed



Recurrent Neural Networks as a surrogate model

- Encoding the initial conditions in a low-dimensional latent space
- Time recurrence in the latent space
- Decoding the latent variable at each time step




Recurrent cells

- Classical cells : LSTM, GRU, ResNet ...
- Must be sufficiently permissive while being conducive to gradient training

Limitations

Stable orbits sometimes learned unintentionally

- For a dissipative dynamical system: no stable orbits, a converging solicitation must lead to a converging solution



Example of RNN having learned stable orbits instead of one of the two equilibrium points

Proposed solution

Recurrent cell architecture structurally incapable of producing stable orbits

- We built a recurrent cell with a learnable internal energy that can never grow without variation of the external solicitation

Continuous cell equation:

$$\begin{cases} E(h, f) = V(h) - h^\top W_f f \\ \dot{h} = A(h) \partial_h E \\ \text{under condition } h_2^\top A(h_1) h_2 \leq 0 \forall h_1, h_2 \end{cases}$$


with (for example) :

$$\begin{cases} M(h) = \sum_{i=1}^{n_{pgd}} r_{n_i}^1(h) r_{n_i}^2(h)^\top \text{ where } r_{n_i}^1(h) \text{ and } r_{n_i}^2(h) \text{ are arbitrary neural networks} \\ A(h) = -(M(h) + M^\top(h))^2 + M(h) - M^\top(h) \\ V(h) = \sqrt[n_0]{\prod_{j=1}^{n_0} V_j(h)} + 1 - 1 \text{ where } V_1, \dots, V_{n_0} \text{ are learnable quadratics functions} \end{cases}$$

Experimentations


Material point in a non-convex potential well

- Simple 1 dof test case
- We aim to predict the horizontal displacement $u(t)$ given oscillating horizontal force $f(t)$
- One or two possible equilibrium points depending on the horizontal effort applied



Results

- Both equilibriums can be properly learned by our architecture
- Unlike LSTM and GRU it can never produce stable orbits




Example of RNN that has correctly learned the two equilibrium points

Hyperelastic beam in finite transformation

- FEM simulation 30 dofs
- We aim to predict the beam displacement over time given a time sequence of high amplitude oscillating force at beam tip

Results

- Our architecture is able to predict the beam displacement even for very long time sequences



Two examples of predicted and targeted sequences

Conclusion and perspectives

- Our architecture has an universal approximator property for hyperelastic structures and a mathematically guaranteed absence of stable orbits
- We were able to train it satisfactorily on two test cases even if the mean error obtained with GRU cells were lower most of the time
- The proposed structure for $A(h)$ and $V(h)$ must be improved to increase the representation power of our architecture